AUTOMATIC COMMERCIAL POOL CLEANERS



TRX 8700 IQ - VORTRAX

ZODIAC® NEW 2025

Specifically designed for intensive use in public pools (hotels, campings, sports centers etc.) with rigid walls up to 25 m length tough, smart and ultra-efficient.

+ **Ultrasonic sensors to detect walls and obstacles.**
+ **High performance brushless electronic motor.**
+ **Kinetic remote control.**
+ **Easy-to-clean brush system.**
+ **Sensor Nav Sytem TM: intelligent and personalised cleaning with anti-tangle compass system without the need of swivel.**
+ **Heavy-duty materials and traction system for intensive use.**
+ **Ultra-powerful and long-lasting suction with easy-to-clean filters.**

3 YEAR WARRANTY*

PROFESSIONAL ADVICE RECOMMENDED

ULTRASONIC SENSOR · Sensor Nav System™ · TRACKS TRACTION

PATENTED CYCLONE SUCTION · iAquaLink CONTROL · PATENTED LIFT SYSTEM®

	Code
Standard Model	WR000598

Accessories

Trolley
Control box
Dual-Stage filter 150 + 60µ (with possibility to use 150µ alone)
Contact Brushes
Free app
Kinetic bluetooth remote control

FOR WHICH TYPE OF POOLS?

Types of pools	Public pools (hotels, campings, sports centers) with rigid walls, up to 25m length
Pool shapes	Rectangular, oval, freeshape
All Floors	Flat, gentle slope, composite slope, diamond shape
Pool surfaces	Tiles, liner, polyester hull, reinforced PVC, painted concrete

DESCRIPTION

Cleaning areas	Floor /walls/ waterline
Number / Length of cleaning cycles	Multiple from 0h30 to 6h00 with preset cycles: -Quick: floor only 1h15 -Smart: floor / walls / waterline (calculated time) -Ultra: floor / walls / waterline (2h45)
Timer / Delayed start	7-days timer / Up to 3h delayed start
Power supply	Autonomous, connected to 230V main supply before the transformer
Steering	Pre-programmed
Drive system	Tracks system drive - 2 brushless motors
Transmission	Gear transmission with reinforced components
Pressure sensor	Yes
Brushes	Yes (Contact + ZZ Brushes)
Lift System	Yes
Full filter indicator	Yes
Remote control	Kinetic bluetooth remote control
Ultrasonic sensors	Yes
Water temperature measure-ment	Yes
Pressure depth sensor	Yes
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	12

TECHNICAL SPECIFICATIONS

Number of motors	3
Control box supply	200-240 VAC ; 50 / 60Hz
Power supply	30 VDC
Operating power	150 W
Cable length / Hose length	30m
Cleaner size (L x W x h)	47 x 51 x 29 cm
Packaging size (L x W x h)	56 x 56 x 46 cm
Cleaner weight	13 kg
Packaging weight	24 kg
Filtering surface and level	1180 cm^3
Filtering capacity	5L
Inlet suction size / /Cleaned width	24.5 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

Fine filter canister 100µ	Fine filter canister 200µ
R0863600	R0863700